



## Prusa i3 MK2 Z-axis reinforcement



Tomaae

[VIEW IN BROWSER](#)

updated 12. 4. 2022 | published 26. 12. 2019

### Summary

Z-axis reinforcement for Prusa i3 MK2 Reinforces Z-axis and helps removing Z-axis wobble for better print quality



7.81 hrs



1 pcs



0.20 mm



0.40 mm



PET



105 g



Prusa MK2/S

[3D Printers](#) > [3D Printers - Upgrades](#)

Tags: [prusa](#) [antivibration](#) [zaxis](#) [zaxisstabilizer](#)  
[reinforcement](#)

Z-axis reinforcement for Prusa i3 MK2

Reinforces Z-axis and helps removing Z-axis wobble for better print quality

### Print instructions

BOM:

2x M8 430mm threaded rods, front Y axes replacement

2x M8 440mm threaded rods, Y to Z axis connection

16x M8 nut

16x M8 washer

4x M3 25mm screw

4x M3 nut (preferably nylon insert locking nuts)

## Model files



**prusa\_i3\_z-axis\_solidifying\_kit.3mf**

## Print files



**prusa\_i3\_z-axis\_solidifying\_kit\_02mm\_petg\_mk2s.gcode**

 PET  0.40 mm  0.20 mm  7.81 hrs  105 g  Prusa MK2/S

## License

This work is licensed under a

[Creative Commons \(4.0 International License\)](#)



**Attribution—Noncommercial—Share Alike**

- 
- ✗ | Sharing without ATTRIBUTION
  - ✓ | Remix Culture allowed
  - ✗ | Commercial Use
  - ✗ | Free Cultural Works
  - ✗ | Meets Open Definition