



Swing-Out Under-Desk Keyboard Tray



ArtSuzhou

[VIEW IN BROWSER](#)

updated 7. 10. 2026 | published 7. 10. 2026

Summary

A 3D printed swing-out keyboard tray support designed to bring the keyboard closer to the user when needed.

[Gadgets](#) > [Computers](#)

Tags: [ergonomic](#) [logitechmx](#) [keyboardmount](#) [limitedmobility](#)
[logitechmxkeys](#) [adaptivedesign](#) [deskinnovation](#)

I designed this **3D printable swing-out keyboard tray support** to make the Logitech MX Mechanical Keyboard easier to position and access, especially for users who may have difficulty reaching a keyboard placed on top of a desk.

The mechanism mounts underneath the desk and allows the keyboard to **swing forward into a comfortable typing position**, then fold back underneath the desk when it is no longer needed.

Unlike a conventional sliding keyboard tray, the articulated arms move the keyboard outward and forward in an arc. This can help bring the keyboard closer to the user without requiring them to reach deeply across the desk.

The design may be useful for people with **limited shoulder or arm mobility, reduced reach, chronic pain, wheelchair seating**

positions, or anyone who needs more flexibility in keyboard placement.

The two support mechanisms use linked arms and synchronized movement to support the tray from both sides. Large release/locking levers are positioned near the front so the mechanism can be operated without reaching far underneath the desk.

The keyboard itself is not modified in any way. It simply rests on the tray, making the system completely reversible.

Two versions are provided: a **full-size version (462 or 480mm)** designed for full-size keyboards such as **Logitech MX**, and a **shorter version (300 mm)** for compact keyboards such as the Logitech Pebble Keys 2.

Features include: swing-out and fold-away movement; under-desk mounting; adjustable keyboard positioning; large, easy-to-operate release levers; mostly 3D printed construction; replaceable individual components; and compatibility with a lightweight printed, wood, acrylic, or aluminum tray.

The example shown uses a lightweight honeycomb-pattern 3D printed platform with my Logitech keyboard. The support mechanism is mounted underneath the desk using common screws and hardware.

I designed this because a fixed desktop keyboard position is not ideal for everyone. Being able to bring the keyboard **closer to the body instead of requiring the user to reach toward the desk** can make a workstation substantially easier to adapt to the individual user.

Accessibility focus: Different reach / limited arm mobility / ergonomic keyboard positioning

Assembly Instructions

The **Left Assembly** and **Right Assembly** are mirrored versions of each other. Assemble both mechanisms first, attach them to the keyboard tray, and then mount the complete tray under the desk.

Parts

(Note: Amazon links for the hardware/parts are provided for reference only. You do not need to purchase from Amazon. All required hardware can typically be found at a local hardware store for less than \$10 total.)

For each side you will need:

- 1 × Upper Bracket
- 1 × Lower Bracket
- 1 × Upper Link Arm — the arm with the locking gear
- 1 × Lower Link Arm
- 1 × Release Lever
- Pivot Screws x 4 (#8 x 3/4 or M4 x 20 mm Self Tapping pan head phillips pan screw)
- Lever Screw x1 (M2.6 x 12mm Self Tapping pan head phillips screw)
- Spring for the release lever (0.6x7x20mm or similar).

You will also need:

- 1 × Keyboard Tray (For the full size version, connect the Left and Right part with 4 #6 x 1/2 (M4 x 12 mm) inch Flat Head Phillips Wood Screws.
- 1 × Back Plate (Optional)
- 4 #6x 1 inch (M4 x 20 mm) Flat Head Phillips Wood Screws suitable for mounting the upper brackets to your desk

1. Assemble the linkage

Start with one side.

Attach **Upper Link Arm** to the **Upper Bracket** using a pivot bolt.

Attach **Lower Link Arm** to the second pivot point on the Upper Bracket.

Do not fully tighten the pivot bolts. The arms need to rotate freely without excessive side-to-side play.

2. Attach the Lower Bracket

Connect the opposite ends of Upper Link Arm and Lower Link Arm to the corresponding pivot points on the **Lower Bracket** use 4mm x 18 mm screws.

Upper Link Arm should be positioned so that the **gear teeth face the release lever**.

Once both arms are attached, move the mechanism through its full range of motion. The two arms work together as a linkage to keep the keyboard tray approximately level as it swings in and out.

Again, tighten the pivot hardware only enough to remove excessive play. Do not clamp the printed parts tightly together.

3. Install the locking lever

Mount the **Locking Lever** onto the Lower Bracket at its pivot point with a 3mmx12mm screw.

Install the spring so that it pushes the lever toward the gear teeth on Upper Link Arm.

Check that:

- The lever naturally engages the gear.
- Pressing the large paddle disengages it.
- The linkage can move while the lever is held.
- Releasing the lever allows it to lock securely into the gear again.

The large paddle is intentionally easy to reach and operate.

4. Repeat for the other side

Assemble the opposite mechanism in exactly the same way using the mirrored right-side parts.

Make sure the two assemblies are true mirror images of each other.

5. Attach the keyboard tray

For the full-size version, the keyboard tray consists of separate left and right sections. Two versions of the Left section are provided to accommodate keyboards up to 462 mm or 480 mm wide, while also allowing users to choose the version that fits their 3D printer's build plate smaller than 250mm.

The Logitech MX Mechanical is approximately 430 mm wide, so the 462mm version works fine.

Align the two tray sections and connect them using **4 × #6 × 1/2" screws** through the provided joining holes. Tighten the screws evenly so the two halves sit flush and the tray remains flat.

An **optional back tray stopper** is also included. Install it along the rear edge of the tray if you want additional protection against the keyboard sliding backward while the tray is moving between the stowed and deployed positions.

The stopper is optional and can be left off if it is not needed for your keyboard setup.

Attach the **Lower Brackets** to the left and right sides of the keyboard tray use #6 x 1 inch screw.

Keep both sides aligned so the tray remains square and level. Before fully tightening the mounting hardware, operate both mechanisms several times to make sure nothing binds.

Install the **Back Plate** at the rear of the keyboard tray. It helps keep the keyboard from sliding backward when the tray is being moved.

6. Mount under the desk

Position the completed assembly underneath the desk and determine the most comfortable location before drilling any holes.

The tray should:

- Clear the front edge of the desk when swinging out.
- Fold completely underneath the desk when stored.
- Be centered with your normal sitting position.
- Have enough clearance for your knees and other equipment under the desk.

Mark the mounting holes through both **Upper Brackets**, then secure the brackets to the underside of the desk using screws appropriate for your desk material.

It is easier to install if another person supports the keyboard tray while the brackets are being screwed into place.

To make it easier to locate the mounting screw positions under the desk, **temporary Mounting Template bracket are provided.**

First, attach the locating brackets to the **left and right sides of the keyboard tray**. Position the tray under the desk where you want it installed and make sure it is centered and has enough clearance to move between the stowed and deployed positions.

Use the locating brackets to mark the mounting screw locations on the underside of the desk.

Then:

1. Mark all mounting-hole locations.
2. Remove or lower the tray as needed.
3. **Pre-drill the mounting holes** using an appropriately sized drill bit for your screws and desk material.
4. Remove the temporary locating/template brackets from the keyboard tray.
5. Position the actual Left and Right tray mechanisms over the pre-drilled holes.

6. Secure both Mounting Brackets to the underside of the desk using the appropriate mounting screws.

Before fully tightening the screws, check that both mechanisms are aligned and that the tray moves freely.

The locating brackets are only used as **installation templates** and are removed before the final tray mechanisms are installed.

7. Final adjustment and testing

Before placing a keyboard on the tray:

1. Swing the tray fully out.
2. Lock it in position.
3. Check that both sides are securely engaged.
4. Release both levers and fold the tray underneath the desk.
5. Repeat several times to make sure the mechanism operates smoothly.

If a joint feels too tight, slightly loosen that pivot bolt. If there is excessive movement, tighten it slightly.

Do not overtighten the pivot bolts — the printed arms must remain free to rotate.

Once everything is moving correctly, place the keyboard on the tray and test it gradually before applying your normal typing pressure.

Full-Size and Short Versions

Two tray sizes are provided:

- **Full-Size Version:** for full-size keyboards and larger keyboard layouts.
- **Short Version:** for compact keyboards such as the Logitech Pebble Keys 2.

The linkage and assembly method are the same for both versions.

Model files



Keyboard Tary Full Size - STL

4 files



keyboard-tray-full-size-left-short.stl



keyboard-tray-full-size-left.stl



keyboard-tray-full-size-right.stl



keyboard-tray-full-size-back-plate.stl



Keyboard Tray Mechanism - STL

10 files



keybaord-tray-mechanism-upper-bracket-left.stl



keybaord-tray-mechanism-upper-link-arm-right.stl



keybaord-tray-mechanism-upper-link-arm-left.stl




keybaord-tray-mechanism-locking-lever-right.stl




keybaord-tray-mechanism-lower-link-arm-right.stl



keybaord-tray-mechanism-lower-bracket-left.stl



keybaord-tray-mechanism-locking-lever-left.stl



keybaord-tray-mechanism-upper-bracket-right.stl



keybaord-tray-mechanism-lower-bracket-right.stl



keybaord-tray-mechanism-lower-link-arm-left.stl



Keyboard Tray Short - STL

2 files



keybaord-tray-short-backplate.stl



keyboard-tray-short.stl



keyboard-tray-full-size.step



keyboard-tray-short.step



keyboard-tray-mechanism.step



keyboard-tray-mounting-template.stl

License

This work is licensed under a
[Creative Commons \(4.0 International License\)](https://creativecommons.org/licenses/by-nc-sa/4.0/)



Attribution—Noncommercial—Share Alike

- ✗ | Sharing without ATTRIBUTION
- ✓ | Remix Culture allowed
- ✗ | Commercial Use
- ✗ | Free Cultural Works
- ✗ | Meets Open Definition