



Spackle Spreader



TimW

[VIEW IN BROWSER](#)

updated 10. 11. 2022 | published 10. 11. 2022

Summary

Applicator for applying and smoothing spackle to fill drywall holes and cracks.



1.55 hrs



1 pcs



0.15 mm



0.40 mm



PLA



17 g



Prusa
MK3/S/S+

[Hobby & Makers](#) > [Tools](#)

Tags: [applicator](#) [drywall](#) [spreader](#) [wallboard](#)

Applicator for applying and smoothing spackle to fill drywall holes and cracks. I tried several hardness vs flexibility for the blade and 0.5 won out. No supports or brim needed. Printed on my Prusa MK3S+ in about an hour and a half so I i damage it, easy and cheap to replace!

Model files



spackle-spreader-05.stl

Print files



spackle-spreader-point5-_015mm_pla_mk3s_1h33m.gcode

🌀 PLA 🌀 0.40 mm ≡ 0.15 mm ⌚ 1.55 hrs ⚖️ 17 g 🖨️ Prusa MK3/S/S+

License ©

This work is licensed under a
[Creative Commons \(4.0 International License\)](#)



Attribution

-
- ✗ | Sharing without ATTRIBUTION
 - ✓ | Remix Culture allowed
 - ✓ | Commercial Use
 - ✓ | Free Cultural Works
 - ✓ | Meets Open Definition