



PRUSA MK3 Filament Guide

 Fredslund

[VIEW IN BROWSER](#)

updated 22. 7. 2021 | published 27. 10. 2020

Summary

Filament guide imbedded in the Z-Axis top part, the only thing you need is a piece of the PTFE tube.



1.46 hrs



1 pcs



0.15 mm



0.40 mm



PET



10 g



Prusa
MK3/S/S+

[3D Printers](#) > [3D Printers - Upgrades](#)

Tags: [upgrade](#) [prusa](#) [prusai3](#) [filament](#) [originalprusai3mk3](#)
[prusai3mk2](#) [filamentguide](#) [prusai3mk3](#) [prusai3mk3s](#)
[upgrades](#) [prusaupgrades](#) [printerupgrades](#)

Check out the 2.0 <https://www.prusaprinters.org/prints/72157-prusa-mk3-filament-guide-20>

Filament guide imbedded in the Z-Axis top part, the only thing you need is a piece of the PTFE tube.

Print instructions

I recommend printing the part in 0.15mm layer height, with at least 3 perimeters and 25% gyroid infill.

once the part is printed, you simply need to cut at small piece of PTFE tube, which can then be bended and put into the two opening, where it will stay in place.

Why the PTFE you say?

because the friction coefficient between the PTFE and the Filament is very low, which means it wont scrape the filament.

good luck & happy printing!!!!

Model files



filament-holder.stl

Print files



filament-holder_015mm_petg_mk3s_1h28m.gcode

⚙ PET 📏 0.40 mm 📏 0.15 mm ⌚ 1.46 hrs ⚖ 10 g 🖨 Prusa MK3/S/S+

License ©

This work is licensed under a
[Creative Commons \(4.0 International License\)](#)



Attribution-ShareAlike

- ✘ | Sharing without ATTRIBUTION
- ✓ | Remix Culture allowed
- ✓ | Commercial Use
- ✓ | Free Cultural Works
- ✓ | Meets Open Definition