



CHTNozzle - ASA/ ABS Tuned X1C Print Profiles for Bambu/Orca-Slicer



Adam L

[VIEW IN BROWSER](#)

updated 9. 8. 2023 | published 9. 8. 2023

Summary

People deserve a better starting point than generic profiles. I hope this ASA collection for CHT nozzles helps others!

[3D Printers](#) > [3D Printers - Upgrades](#)

Tags: [filament](#) [abs](#) [tuning](#) [profile](#) [asa](#) [x1](#) [bambu](#)
[chtnozzle](#) [bambulabx1](#) [bambulab](#) [bambulabx1carbon](#) [x1c](#)
[p1p](#) [p1s](#)

Important note: This collection is for **brass CHT-Style nozzle (0.4 mm)** with the Bambu printers.. NOT the stock ones. These CHT-style nozzles allow for higher flow/faster printing than the stock hotend is able to achieve. If you want one, you'll need to buy a kit from aliexpress or some local retailer. Note that these are NOT official BondTech CHT nozzles, but a chinese clone for the X1/P1P. I'd buy official ones if I could to support BondTech, but they haven't made anything available. I've included a picture of the nozzle as part of the image so nobody gets confused.

Change log:

- (8/2/23): Added Prusament Sapphire Blue (ASA) (8/2/23). VFR =30.5

- (8/9/23): I decided not to shrink-compensate my profiles because I think it's likely to introduce confusion for people who are used to scaling for these filaments, but for people who want to combat the common shrinkage in ABS/ASA, please [see my other model here that helps you calibrate](#).

What this is:

This is a collection of all of my PETG filament profiles for all filaments I've used of this type. I happen to have a decent amount of [California Filaments](#) because I've found that brand works well with this printer, and you can push the flow rates higher with it than some others.

I will update it as I tune new filament brands and colors. They are generally tuned for **flow rate**, **pressure advance**, and **temperature** and **volumetric flow limits** and **overrides**. They're a good working starting point for anyone struggling with a filament. I've also tuned other types of filaments (see [my models here](#)) and you should find, by category:

Standard Nozzle (0.4 mm , Hardened Steel, should work for P1P/P1S as well)

- [TPU / Flexibles](#)
- [Nylon/PA and PACF variants](#)
- [Polycarbonate & Polycarbonate-CF](#)
- [PLA / PLA + / Silk PLA](#)
- [ABS / ASA](#)

CHT-Nozzle (0.4 mm , Brass)

- [PETG](#)
- [PLA](#)
- [TPU](#)

How to use:

These 3MF files are designed for use in Orcaslicer/Bambuslicer, but will work best in Orcaslicer, because it supports using a fixed pressure-advance value in the slicer.

- Load the 3MF file for the filament of your choosing. Files are named as **<Brand>_<Color>_<Type>.3mf**.
- (optional, recommended): Save the filament and/or print presets for your own use to your user presets for future use.
- Remove the calibration cube dummy object and put your desired object in.

- **Print! But, turn off flow calibration option in your prints!** The more reliable PA value stored in the filament profile will be used instead, and you can skip the wasted startup time, too!



- If you want to use these in Bambu slicer, you won't get the PA values applied automatically sadly, and you'll have to do that with a **manual GCODE in the filament's start GCODE**. This is really annoying to do for each filament, but it does work. However I suggest you try Orcaslicer for this reason.

Important notes:

- These profiles are tuned on an X1C, with a brass CHT-style 0.4 nozzle installed, for use with a range of layer heights. **If you have a different nozzle size or nozzle kind (steel/brass), these will not be good profiles. See my the links above for standard nozzles.**
- Each 3MF also contains some of my own optimized settings for 0.16 mm prints, which I typically use, but these tuned filament profiles are designed/tuned to work across a variety of different print profiles.

Background:

I use the **Orca Slicer** variant of Bambu's slicer because it offers finer-grained control over the slicing process and makes tuning and using tuned filament profiles much easier than Bambu's official slicer, which lacks good calibration routines for some of the most important variables in good printing: **flow rate**, **pressure advance**, and **temperature** and **volumetric flow limits**.

This is particularly true for Bambu's Pressure Advance (**they incorrectly call this "flow"**) calibration, which forces you to run it every time and is unreliable, particularly on the popular textured PEI surface.

Each of these profiles has been tuned for:

- **Flow rate** (aka extrusion multiplier)
- **Pressure advance** (aka linear advance)
- **Temperature** (with temp towers)
- **Volumetric flow limits** (my settings are a little conservative based on printing the max volumetric flow rate calibration inside Orcaslicer)
- **Overrides** (I typically try to avoid using these unless I have to)

This remix is based on



- PETG - Tuned X1C Print Profiles for Bambu/Orca-Slicer

by Adam L

Model files



chtnozzle_prusament_sapphireblue_asa.3mf

License

This work is licensed under a
[Creative Commons \(4.0 International License\)](#)



Attribution-ShareAlike

-
- ✗ | Sharing without ATTRIBUTION
 - ✓ | Remix Culture allowed
 - ✓ | Commercial Use
 - ✓ | Free Cultural Works
 - ✓ | Meets Open Definition