



Lack Enclosure Filament Slot Guide



CWCDesigns

[VIEW IN BROWSER](#)

updated 12. 4. 2022 | published 19. 10. 2019

Summary

I added a cement paver to the inside of my Ikea Lack enclosure but it made my printer come very close to the top.

[3D Printers](#) > [3D Printers - Upgrades](#)

Tags: [prusa](#) [prusai3](#) [filament](#) [3dprinting](#) [ikealack](#)
[filamentspoolholder](#) [lack](#) [filamentguide](#) [3dprinter](#)
[prusai3mk3](#)

I added a cement paver to the inside of my Ikea Lack enclosure but it made my printer come very close to the top. This would have caused some filament issues for tall prints and would have easily snapped some filament. I used the existing holes from the original lack enclosure and cut out all the space between them making a slot that is 275mm by 10mm. Just used a utility knife to make the cut.

Print instructions Licence: Creative Commons - Attribution Category: 3D Printing Print Settings

Printer Brand: Prusa

Printer: i3 MK3

Rafts: No

Supports: No

Resolution: .20

Infill: 20%

Model files



filament_slot_guide.stl

[Find source .stl files on Thingiverse.com](#)

License

This work is licensed under a
Creative Commons (4.0 International License)



Attribution

-
- ✗ | Sharing without ATTRIBUTION
 - ✓ | Remix Culture allowed
 - ✓ | Commercial Use
 - ✓ | Free Cultural Works
 - ✓ | Meets Open Definition